

## STANDARD MANUAL STACKER

Ideal and economic choice for manual transport and lifting, with its different mast options (1600, 2500, 3000 mm) and diverse lifting capacity (500kg, 1000kg, 1500kg), 1500kg enables to deal with a large number of applications in the warehouse or any other facilities. For example, with the lift capacity of 1000 kg and lifting height of 1600 mm, therefore the truck is an ideal and economic choice suitable for first level stacking.

| Hand Stacker                          |    | 1KG=2.2LB 1INCH=25.4MM |             |             |
|---------------------------------------|----|------------------------|-------------|-------------|
| ITEM/TYPER                            |    | SFH10                  | SFH15       | SFHD10      |
| Capacity Q                            | Kg | 1000                   | 1500        | 1000        |
| Min. fork height h <sub>0</sub>       | mm | 85                     | 85          | 85          |
| Max. fork height h <sub>1</sub>       | mm | 1600                   | 1600        | 2500        |
| Min. mast height h <sub>2</sub>       | mm | 1980                   | 1980        | 1830        |
| Size of fork e*s                      | mm | 150/160x80             | 150/160x80  | 150/160x80  |
| Length of fork L                      | mm | 900/1150               | 300/1150    | 900/1150    |
| Width of overall fork (adjust/fixe) s | mm | 330-740/850            | 330-740/550 | 330-740/550 |
| Radius of gyration                    | mm | 1250/1380              | 1250/1380   | 1250/1380   |
| Weight                                | Kg | 220                    | 280         | 300         |
| Fork rollers                          | mm | ∅74x70                 | ∅74x70      | ∅74x70      |
| Big wheel                             | mm | ∅180x50                | ∅180x50     | ∅180x50     |

Conforms to EN1757-1



- Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller.
- Optional choice of fixed fork (550X1150mm) and adjustable fork (330-740X900mm).
- We can offer additional protection for the operator through foot protection on the steering rollers.
- Safe parking in any situation with mechanical parking brake.
- Optional tiller pumping lifting and foot pedal lifting

